WATER QUALITY 2022 Report



Este informe contiene informacion muy importante sobre su agua potable. Traduzcalo o hable con alguien que lo entienda bien.

Water provided by the Carlsbad Municipal Water District meets all 2022 state and federal drinking water standards. This report provides detailed water quality test results and more information about where Carlsbad's water comes from.

Where our water comes from

CMWD currently imports 83% of its drinking water. The water supply begins hundreds of miles away as snow melt or rainfall that flows into rivers. The two main water sources are the Colorado River, where the water is transported through the Colorado River Aqueduct, and Northern California, where water moves through the California Aqueduct (also known as the State Water Project).

Water from these sources is treated by the Metropolitan Water District of Southern California at its Lake Skinner Treatment Plant in Riverside County and by the San Diego County Water Authority. After rigorous treatment, the water travels through pipelines owned by the San Diego County Water Authority, and is then purchased and distributed by CMWD to its customers.

The Claude "Bud" Lewis Carlsbad Desalination Plant produces 17% of Carlsbad's water through the San Diego County Water Authority, which blends the water with the region's imported water supply and delivers it to water agencies throughout San Diego County.

What's in your water before it's treated?

Both tap and bottled drinking water comes from oceans, rivers, lakes, streams, ponds, springs and wells. As water travels over the surface of the land or through the ground, it dissolves naturally occurring minerals and, in some cases, picks up substances resulting from the presence of animals or from human activity.

Contaminants that may be present in source water include:

- Microbial contaminants, such as viruses and bacteria that can come from wastewater treatment plants, septic systems, agricultural livestock operations and wildlife.
- Inorganic contaminants, such as salts and metals, that can be naturally occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining or farming.

- Pesticides and herbicides, that can come from a variety of sources such as agriculture, urban stormwater runoff and residential uses.
- Organic chemical contaminants, including synthetic and volatile organic chemicals, that are byproducts of industrial processes and petroleum production, and can also come from gas stations,



urban stormwater runoff, agricultural application and septic systems.

• Radioactive contaminants, that can be naturally occurring or be the result of oil and gas production and mining activities.

Continued on page 4

2022 CARLSBAD WATER QUALITY ANALYSIS

					50/10			1	INALIS	15
Parameter	Units	State or Federal MCL [MRDL]	PHG (MCLG) [MRDL]	State DLR	Range Average	Skinner Plant Effulent	Twin Oaks Plant	CMWD System Samples	Carlsbad Desal Plant	Major Sources in Drinking Water
Demonstration Device at Western	~				Range	0 - 43	NA	NA	NA	
Percent State Project Water	%	NA	NA	NA	Average	NA	NA	NA	NA	
				P	RIMARY STANDA	RDSMandator	y Health-Related	Standards		
						CLARIT	Y			
Combined Filter	NTU	TT=1			Highest	0.05	0.005 - 0.029	NA	0.05	
Effluent Turbidity(a)	%	TT (a)	NA	NA	% ≤ 0.3	100%	100%	NA	100.0%	Soil runoff
						MICROBIOLO	GICAL			<u>I</u>
	<u> </u>				Range	NA	ND	NA	0	
Total Coliform Bacteria (b)	%	5.0	MCLG=0	NA	Average	NA	ND	NA	ND	Naturally present in the environment
					-					
E. coli (c)	NA	TT	MCLG=0	NA	Positive sample	NA	ND	ND	ND	Human and animal fecal waste
				r	-	INORGANIC CH	r			L
Arsenic	ppb	10	0.004	2	Range	ND	2	NA	ND	Natural deposits erosion, glass and electronics, production wastes
					Average	ND	NA	NA	ND	
2021 Copper Samples (e)	ppm	AL = 1.3	0.3	0.05	No.>AL 90%ile	NA NA	NA ND	0	ND ND	Internal corrosion of household pipes natural deposits erosion,next set of samples to be taken in 2024
			Control Ban		90%ile	NA	NA	NA NA	NA	-
Fluoride (d)	Control Range Optimal Fluoride Level				NA	NA	NA	NA		
		00								
Treatment-related Fluoride	ppm	2.0	1	0.1	Range	0.6 - 0.8	0.5 - 0.7	NA	ND - 0.797	Erosion of natural deposits water additive that promotes strong teeth
					Average	0.7	0.6	NA	0.667	nate dualitie and promotes strong teem
2021 Lead Samples (e)	ppb	AL = 15	0.2	5	No.>AL	0	0	0	0	House pipes internal corrosion; erosion of natural depos
pres (c)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				90%ile	ND	ND	1.4	ND	its, next set of samples to be taken in 2024
Nitrate	ppm	10	10	0.4	Range	ND	ND	NA	ND	Runoff and leaching from fertilizer use, septic tank and
	L		l		Average	ND	ND	NA	ND	sewage, natural deposits erosion
						RADIOLOGI	CALS			
Uranium	pCi/L	20	0.43	1	Range	ND - 2	ND	NA	ND	Erosion of natural deposits
	P				Average	2	ND	NA	ND	
		DISI	NFECTION B	Y-PRODUC	TS, DISINFECTA	NT RESIDUALS,	AND DISINFECT	ION BY-PROD	UCT PRECURSO	RS (o)
Total Trihalomethanes (f) (TTHM)	ppb	80	NA	1.0	Range	14 - 29	21 - 40	0.00 - 35.0	ND	By-product of drinking water chlorination
					Highest LRAA	20	40	19	ND	-,
Haloacetic Acids (HAA5) (f)	ppb	60	NA	1.0	Range	6.0 - 13	ND - 6.1	0.00 - 7.1	ND	By-product of drinking water chlorination
	pps				Highest LRAA	9.0	6.1	3.0	ND	by productor driming match chronination
Total Chlorine Residual	ppm	[4.0]	[4.0]	NA	Range	NA	2.6 - 3.5	0.40 - 3.50	2.95 -3.58	Drinking water disinfectant added for treatment
					Highest RAA	NA	3.1	2.35	3.18	
Bromate (g)	ppb	10	0.1	1.0	Range	ND - 5.5	1.6 - 5.8	NA	NA	By-product of drinking water ozonation
					Highest RAA	1.2	3.0	NA	NA	
					SECONDAR	Y STANDARDS	Aesthetic Stand	ards		
Chloride	ppm	500	NA	NA	Range	98 - 106	110 - 110	NA	20 - 119	Runoff leaching from natural deposits
					Sample	102	110	NA	90	seawater influence
Color	Units	15	NA	NA	Range	1 - 2	ND	NA	ND	Naturally-occurring organic materials
					Average	2	ND	NA	ND	
Odor Threshold	TON	3	NA	1	Range	1	ND	NA	ND	Naturally-occurring organic materials
					Average	NA	ND	NA	ND	
Specific Conductance	µS/cm	1600	NA	NA	Range	944 - 1030	NA	NA	345.4 - 484.58	Substances that form ions in water seawater influence
					Average	987	980	NA	400.77	
Sulfate	ppm	500	NA	0.5	Range	206 - 229 218	210 - 220	NA NA	13 - 15 13.5	Runoff leaching from natural deposits Industrial wastes
					Average Range	591 - 651	NA	NA	138 - 285	
Total Dissolved Solids (TDS)	ppm	1000	NA	NA	-	621	610	NA	210.7	Runoff leaching from natural deposits seawater influence
					Average			INA	210.7	
						OTHER PARA				
					Para	CHEMIC/ 119 - 128	NA	NA	46 - 87	
Alkalinity	ppm	NA	NA	NA	Range	119-128 124	NA 130	NA NA	46 - 87 61.0	
	-				Average	124	130 NA	NA NA	61.0 0.47 - 0.91	
Boron	ppb	NL=1,000	NA	100	Range Average	130	NA 130	NA NA	0.47 - 0.91	Runoff leaching from natural deposits, Industrial wastes
					Range	63 - 71	67 - 68	NA	16.76 -30.44	
Calcium	ppm	NA	NA	NA	Sample	67	68	NA	20.69	
					Range	0,	250 - 440	NA	20.89 NA	
Chlorate	ppb	NL=800	NA	20	Average	75	336	NA	NA	By-product of drinking water chlorination Industrial processes
					Range		0.03 - 0.22	NA	NA	
Chromium VI (h)	ppb	10	0.02	1	Average	ND	0.11	NA	NA	Runoff leaching from natural deposits; discharge from industrial waste factories
Companying (1)					Range	12.4 - 12.5	NA	NA	10.34-11.24	Elemental belance in water off at a live
Corrosivity (i) (as Aggressiveness Index)	AI	NA	NA	NA	Average	12.4	13	NA	10.53	Elemental balance in water; affected by temperature, other factors
Corrosivity (j)					Range	0.56 - 0.75	NA	NA	0.04 - 0.59	Elemental balance in water affected
(as Saturation Index)	SI	NA	NA	NA	Average	0.66	0.82	NA	0.23	by temperature & other factors
					Range	263 -282	NA	NA	41.9 - 76.3	
Hardness	ppm	NA	NA	NA	Average	272	270	NA	51.7	
					Range	24 - 26	25 - 25	NA	0.95 - 1.6	
Magnesium	ppm	NA	NA	NA	Sample	25	25	NA	1.26	
					Range	8.1 - 8.2	8.0 - 8.7	NA	8.34 - 8.71	
рН	рН	NA	NA	NA	Average	8.2	8.3	NA	8.53	
.					Range	4.4 - 4.8	4.7 - 4.8	NA	0 - 31.015	
Potassium	ppm	NA	NA	NA	Average	4.6	4.8	NA	6.811	
Cadlin		NA	NA	NA	Range	96 - 103	98 - 98	NA	52.7 - 64.6	
Sodium	ppm	NA	NA	NA	Average	100	98	NA	58.9	
тос	ppm	тт	NA	0.30	2.3 - 2.6 2.5	2.2 - 2.7 2.5	1.3 - 3.3 2.4	NA	NA	Various natural and man-made sources
					4.4	ND	2.4 ND	NA	NA	
N-Nitrosodimethylamine (NDMA)	ppt	NL = 10	3	2	4.4 NA	NA	ND	NA	NA	By-product of drinking water
	1		1	L						l

How to read this report

As you read the water quality tables in this report, compare the level of contaminants found in the "Skinner Plant", "Twin Oaks Valley Plant", and "Desal plant" and CMWD system samples columns with the standards set for them in the MCL and PHG columns. The CMWD met all drinking water standards in 2022.

The following are key terms to help you understand the standards used to measure drinking water safety.

Maximum Contaminant Level (MCL) The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste and appearance of drinking water.

Maximum Contaminant Level Goal (MCLG) The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency.

Public Health Goal (PHG) The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the California Environmental Protection Agency.

Maximum Residual Disinfectant Level (MRDL) The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

Abbreviations

7100101	lations
AI	Aggressiveness Index
AL	Action Level
CDPH	California Department of Public Health
CFE	Combined Filter Effluent
CFU	Colony-Forming Units
DBP	Disinfection By-Products
DLR	Detection Limits for purposes of Reporting
MCL	Maximum Contaminant Level
MCLG	Maximum Contaminant Level Goal
MFL	Million Fibers per Liter
MRDL	Maximum Residual Disinfectant Level
MRDLG	Maximum Residual Disinfectant Level Goal
Ν	Nitrogen
NA	Not Applicable
ND	Not Detected
NL	Notification Level
NTU	Nephelometric Turbidity Units
pCi/L	picoCuries per Liter
PHG	Public Health Goal
ppb	parts per billion or micrograms per liter (μg/L)
ppm	parts per million or milligrams per liter (mg/L)
ppq	parts per quadrillion or picograms per liter (pg/L)
ppt	parts per trillion or nanograms per liter (ng/L)
RAA	Running Annual Average; highest RAA is the highest of all Running Annual Averages calculated as average of all the samples collected
	within a 12-month period
SI	Saturation Index (Langelier)
TOC	Total Organic Carbon
TON	Threshold Odor Number
TT	Treatment Technique is a required process intended to reduce the level of a contaminant in drinking water
μS/cm	microSiemen per centimeter; or micromho per centimeter (µmho/cm)

Required information for lead

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing.

CMWD is responsible for providing high quality drinking water but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at <u>www.epa.gov/safewater/lead</u>. CMWD has complied and meets Lead and Copper standards.

Maximum Residual Disinfectant Level Goal (MRDLG) The level of a

drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Primary Drinking Water Standard (PDWS) MCLs and MRDLs for

contaminants that affect health along with their monitoring and reporting requirements, and water treatment requirements.

Treatment Technique

A required process intended to reduce the level of a contaminant in drinking water.

Regulatory Action Level The

concentration of a contaminant which, if exceeded, triggers treatment or other requirements that a water system must follow.

This report can be downloaded from www.carlsbadca.gov/water-guality-report.

Footnotes

 a) (Skinner) As a Primary Standard, the turbidity levels of the filtered water were < 0.3 NTU in 100% of the online measurements taken each month and did not exceed 1 NTU for more than one hour.

The turbidity levels for grab samples at these locations were in compliance with the Secondary Standard. (Twin Oaks) The turbidity level from the CFE of the membranes shall be < 0.1NTU in 95% of the measurements taken each month and shall not exceed 1.0 NTU at any time. Turbidity, a measure of the cloudiness of water, is an indicator of treatment performance.

- b) Total coliform MCLs: No more than 5% of the monthly samples may be total coliform positive. Compliance is based on the combined distribution system sampling. In 2022, 1,560 samples were analyzed with no positive samples. The MCL was not violated.
- c) E. coli MCL: The occurrence of two consecutive total coliformpositive samples, one of which contains E. coli, constitutes an acute MCL violation. The MCL was not violated.
- d) Skinner and Twin Oaks were in compliance with all provisions of the State's Fluoridation System Requirements.
- e) Lead and copper are regulated by Action Levels under the Lead and Copper Rule, which requires water samples to be collected at the consumers' tap. If action levels are exceeded in more than 10% of the samples, water systems must take steps to reduce these contaminants.
- f) Twin Oaks/Skinner met all provisions of the Stage 1 Disinfectants/ Disinfection By-Products (D/DBP) Rule. Compliance was based on Locational RAA. Average and range for the treatment plant effluent were taken from daily and monthly samples for TTHM and HAA5.
- g) Twin Oaks running annual average was calculated from quarterly results of monthly and daily samples.
- h) Chromium VI reporting level is ND, which is below the state DLR of 1 ppb.
- AI <10.0 = Highly aggressive and very corrosive water AI >12.0 = Non-aggressive water AI (0.14 - 13.0) = Moderately aggressive water
- Positive SI index = non-corrosive; tendency to precipitate and/or deposit scale on pipes. Negative SI index = corrosive; tendency to dissolve calcium carbonate.

The U.S. Environmental Protection Agency and the State Water Resources Control Board have regulations that limit the amount of certain contaminants allowed in water provided by public water systems to ensure that tap water is safe to drink. Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the U.S. EPA's Safe Drinking Water Hotline at 800-426-4791.

CMWD has sampled all required data including entry points in the distribution system for the fourth Unregulated Contaminant Monitoring Rule (UCMR 4) contaminants in 2020. The analytical results for UCMR are stored in the National Contaminant Occurrence Database for drinking water, which can be found online at <u>www.epa.gov/sdwa/national-contaminant-occurrence-database-ncod</u>.

Water conservation

Carlsbad encourages residents and businesses to continue making water conservation a way of life. With water being a precious and limited resource, Carlsbad is doing our part by making water conservation and the efficient use of water a major priority. Even the simplest changes to daily routines make a difference.

Do your part by following the water conservation tips below and visit <u>www.carlsbadca.gov/conservation</u> for programs, incentives, water rules, and more tips and resources.

Indoor

- Take short showers or fill the bathtub halfway
- Turn water off when brushing teeth or shaving
- Wash only full loads of clothes
- Fix leaks (toilets, faucets, etc.)
- Install high-efficiency fixtures

Outdoor

- Install drip-irrigation
- Adjust sprinklers to reduce water lost from overspray onto impervious surfaces
- Water during cool parts of the day to reduce evaporation
- Install a smart irrigation controller
- Convert to a native landscape
- Repair broken sprinkler heads and/or irrigation lines (do not irrigate until repair is made)



Powell reservoir on the Colorado river

How to contact us

This report covers testing for contaminants in 2022. For questions or concerns regarding the quality of Carlsbad's drinking water, contact CMWD at 442-438-2722 or email water@carlsbadca.gov.

CMWD Board meetings are held in conjunction with the Carlsbad City Council on an as needed basis on Tuesday evenings. Agendas may be obtained



at <u>www.carlsbadca.gov</u> or Carlsbad City Hall, 1200 Carlsbad Village Drive. Comments regarding drinking water are always welcome by the CMWD Board of Directors.

This report can be downloaded from www.carlsbadca.gov/water-quality-report.

Carlsbad Municipal Water District

5950 El Camino Real, Carlsbad, CA 92008 Hours: Monday through Friday, 8 a.m. to 5 p.m. 442-438-2722 • <u>water@carlsbadca.gov</u>

Additional sources for water quality information:

San Diego County Water Authority 858-522-6600 • <u>www.sdcwa.org</u>

Metropolitan Water District of Southern California 800-225-5693 • <u>www.mwdh2o.com</u>

State Water Resources Control Board Division of Drinking Water & Environmental Management

619-525-4159 • www.waterboards.ca.gov

U.S. Environmental Protection Agency

Office of Ground Water & Drinking Water Safe Drinking Water Hotline: 800-426-4791 • <u>www.epa.gov/watersense/</u> state-water-facts

